

# Performance Beyond Expectations



**END SUCTION PROCESS PUMP** 



### **APPLICATIONS**


- Paper stock
- Fibrous pulp & effluent
- Fibrous effluent
- Waste water
- De-watering & de-inking
- Solid entrained liquor
- Chemical / process liquor
- Food process
- Sugar process
- Abattoir

CRI's commitment to deliver Reliable product to customers, enriched by acquisition of UK based Pumps & Process Systems design and its innovative state of the art manufacturing facility.

ECP Series - Rugged and high quality, Horizontal single stage, End Suction, Centrifugal, Foot mounted pumps designed as per manufacturer standard to pump viscous and contaminated liquids, pulp with consistency upto 8%.

12+ wholly owned subsidiaries spread across all continents with manufacturing / assembly and technical service capabilities, to ensure timely delivery and service

#### FEATURES & BENEFITS



Integrated connecting frame\*with Bearing cover - Reduce component & enhance reliability



External Shim set arrangement for impeller clearance adjustment -Restores pump efficiency

Large oil sump with Oil mist / Oil bath lubrication -**Increases MTBF** 



Graphite Impregnated PTFE / Single or Double Mechanical seal -**Environment Safety** 

Bull nose type open impeller -Low NPSH and avoids risk of clogging

Accurately contoured Suction wear plate -Prolonged wear life

- 12 pump sizes with 3 bearing frame assembly ensures spare parts interchangeability, reducing inventory cost
- Additional corrosion allowance for extended wear life
- Vertical sump configuration also available



ECP - REV 2 - FLYER - 10/19





## **TECHNICAL SPECIFICATIONS**

#### 50Hz

| - | Flow                 |   | Upto 2500 m³/h                                |
|---|----------------------|---|---|
|   | Head                 | : | Upto 100 m                                    |
|   | Power                |   | 315 kW  |
|   | Solid handling sizes | : | 95 mm   |
| - | Outlet size          | : | 350 mm  |
| - | Liquid temp.         | : | Upto 90°C**                                   |
| - | Pressure             | : | Upto 16 bar                                   |
|   | MOC                  | : | Stainless Steel, Hi - Alloy Steel & Cast Iron |

#### Note:

- \*Patent pending
- \*\*Contact manufacturer for temperature above 90°C

## C.R.I. PUMPS (PVT) LIMITED

(International Division)

7/46-1, Keeranatham Road, Saravanampatty,

Coimbatore - 641 035. India. Phone: +91-422-7117310, 7117312.

Fax: +91-422-7117300,

e-mail: cri@crifluidsystems.com website: www.crifluidsystems.com Authorized dealer